

GD170-PV Series

Solar Pump Controller

GD170-PV is the new generation of solar pump controller. It has compact structure and outstanding performance in one. The advanced MPPT function makes sure providing the most energy efficient operation of the pump, and rich protection functions ensure the smooth and safe operation.

In summary, it provides a excellent balance of Easy Installation, Easy operation, Advanced pump-control capacity.





Applications









Type Selection

GD170 - 5R5 - 4 - PV









No.	Sign	Description	Remarks	
1	GD170	Product abbreviation	GD170	
2	5R5	Power range	5R5: 5.5k W	
3	4	Voltage degree	4: AC 3PH 380V (-15%)-440(+10%)	
4	PV	Industrial code	PV stands for solar pump.	

Product Specification

DC input	10.		
Max DC voltage(V)	800		
Start voltage(V)	300		
Min. work voltage(V)	250		
Recommended MPPT voltage(V)	300~750		
Recommended input work voltage(V)	550		
AC input			
Input voltage(Vac)	/ martine authorized fr		
Input frequency(Hz)			
AC output			
Output voltage(Vac)	0-input voltage		
Output frequency(Hz)	0-400		
Control performance			
Motor type	Asynchronous and synchronous		
Overload capability	120% of rated current: 1 minute		
Overload Capability	150% of rated current: 10 seconds		
Others			
Protective degree	IP20		
Cooling method	Forced air cooling		
Interface	LED keypad		
Professional function			
Protection function	Underload or phase loss protection		
MPPT function	Automatic factory setting		
Auto run/stop	Sleep when the light is weak, and wake up when the light is strong		
W ater level monitor	Sleep when the water is full, and wake up when the water level is low		
Certification			
Certification standard	IEC62109-1/IEC62109-2/IEC61683		

Product Parameters

Voltage	Model	Rated output power (kW)	Max. DC input current (A)	Rated input current (A)	Rated output current (A)	Product dimension (mm)	
	GD170-2R2-4-PV	2.2	12	5.8	5.5	80*185*143.5	
	GD170-004-4-PV	4.0	16.5	13.5	9.5	80"185"143.5	
	GD170-5R5-4-PV	5.5	24	19.5	14	146*256*166.5	
	GD170-7R5-4-PV	7.5	23.9	25	18.5	140 200 100.5	
3PH	GD170-011-4-PV	11	30.6	32	25		
380 V	GD170-015-4-PV	15	39.2	40	32	170*320*196	
	GD170-018-4-PV	18.5	49	47	38		
	GD170-022-4-PV	22	50	56	45	200*340.6*183.3	
	GD170-030-4-PV	30	60	70	60		
	GD170-037-4-PV	37	81	80	75	250*400*202	
	GD170-045-4-PV	45	90	98	92	200 400 202	



Service line:86-755-23535967 E-mail:overseas@invt.com.cn Website:www.invt.com